

BLACKLIGHTS

UV LIGHTS

Magnaflux designs our UV lights to meet standard specifications first and foremost. Nevertheless, we do work for operator comfort. Magnaflux formulates and manufactures the materials to fluoresce at peak intensity of 365 nanometers. In turn, we take care to design our lights to have peak output at the same 365 nanometers, while filtering out the nonconforming light.

ZB-100F HAND-HELD, FAN-COOLED BLACK LIGHT

ZB-100F Features

- 100 Watt reflective light source
- Fan cooled, cool to the touch
- Cooler running means longer bulb life
- 4000+ Microwatts/Centimeter Squared @ 15"
- White Light Emission, less than 1 foot candle @ 15"
- Weight of hand Held Light Only 3 Lbs (1.4 kg)
- 15 foot (4.6 m) cord from Lamp to Transformer
- 12 foot (3.7 m) cord from Transformer to Supply end
- Ground Fault Circuit Interrupt protection (110/115V only)
- Available voltages: 110v/50 Hz, 115v/60Hz, 220v/50Hz, 230v/60 Hz



ZB-100 F MB—MAG SHOT BLACK LIGHT

All the Features of the ZB-100F PLUS a button conveniently located in the handle, this button is ready to integrate into any of our standard MPI units to trigger the magnetizing current. Or, we can assist you in integrating the new black light into existing equipment. The black light can start rinse cycles on Zyglo Systems, act as a remote trigger on power packs, used to activate touch up developer, or to prompt a parts counter. The possibilities are only limited by the user.

ZB-150 FSB SELF-BALLASTED BLACK LIGHT

ZB-150 FSB Features

- 150 Watt, self ballasted, reflective light source
- Fan cooled, cool to the touch
- Cooler running means longer bulb life
- 4000+ Microwatts/Centimeter Squared @ 15"
- White Light Emission, less than 1 foot candle @ 15"

- Weight of Hand Held Light Only 4 Lbs (1.9 kg)
- 12 foot (4.6 m) cord from Lamp to plug
- Ground Fault Circuit Interrupt protection
- Available voltages: 115v/60Hz

Uses 150w Self-Ballasted Replacement Bulb

